



Fire Protection Products

3M™ Smoke and Sound Tape SST

Product Data Sheet

July 2017

Product Description

3M™ Smoke and Sound Tape is a self-adhered membrane that provides a tough, elastomeric coating. This product has a unique pressure-sensitive adhesive that aggressively sticks and stays stuck to a wide variety of substrates at both high and low temperatures, and will even adhere to damp surfaces. This material is used to provide a hot and cold smoke seal as well as help reduce the transmission of sound.

Product Features

- Elastic material maintains performance with up to $\pm 50\%$ movement capabilities
- Paintable
- Creates an effective barrier to mitigate smoke and toxic gas spread, L-rating of less than 1 CFM/30.48 cm (linear foot) at ambient and 204°C (400°F)
- High-tack adhesive sticks and stays stuck to most common building materials – exceeds the AAMA 711 minimum for adhesion in peel
- Can be installed in temperatures as low as -18°C (0°F) and as high as 49°C (120°F)
- Unique adhesive even adheres to damp surfaces

Applications

3M™ Smoke and Sound Tape is ideal for providing a smoke seal for construction joints, as well as some through-penetration applications in non-fire-rated wall and floor assemblies, including smoke partitions and acoustic assemblies.

Specifications

3M™ Smoke and Sound Tape shall be tested to the criteria of ASTM E84/UL 723 Standard Test Method for Surface Burning Characteristics of Building Materials, ASTM E90 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements, and ASTM E413 Classification for Rating Sound Insulation. 3M™ Smoke and Sound Tape shall meet the requirements of the IBC, IRC, IFC, IPC, IMC, NFPA 5000, NEC (NFPA 70), NFPA 101 and NBCC.

3M Fire Protection Products

3M™ Smoke and Sound Tape SST

Performance and Typical Physical Properties	Sizes Available	51 mm x 2.8 m (2 inches x 75 feet)	24 rolls/case	
		101 mm x 22.8 m (4 inches x 75 feet)	12 rolls/case	
		202 mm x 22.8 m (8 inches x 75 feet)	4 rolls/case	
		303 mm x 22.8 m (12 inches x 75 feet)	4 rolls/case	
	Coverage	1.16 sq m/roll (5 cm) / 12.5 sq ft/roll (2 in) 2.32 sq m/roll (10 cm) / 25 sq ft/roll (4 in) 4.645 sq m/roll (20 cm) / 50 sq ft/roll (8 in) 6.96 sq m/roll (30 cm) / 75 sq ft/roll (12 in)		
	Surface Burning Characteristics (ASTM E84/CAN / ULC S102)	Flame Spread Index: 10 Smoke Developed Value: 10		
	Adhesion (L/cm or oz/in width, per ASTM D3330)	To concrete: 1.63 L/2.54 cm (55 oz/in) To gypsum: 1.63 L/2.54 cm (55 oz/in) To stainless steel: 1.77 L/2.54 cm (60 oz/in) To anodized aluminum: 2.07 L/2.54 cm (70 oz/in) To OSB: 1.47 L/2.54 cm (50 oz/in) To Vinyl: 1.77 L/2.54 cm (60 oz/in) To Polyethylene: 1.33 L/2.54 cm (45 oz/in)		
	STC Rating* (ASTM E90/ASTM E413)	54 in a 54 rated wall		
	Mold and Mildew Resistance (ASTM G21/ASTM D4300)	0% growth		
	Tape Thickness	0.25 mm (10 mils)		
	Service Temp. Range	-40 to 116°C (-40 to 240°F)		
	Tensile Strength (psi) (ASTM D882)	>2100		
	Elongation % (ASTM D882)	>500		
Water Vapour Transmission (ASTM E96/E96M)	0.19 perms			

*when installed using mineral wool or ½ in. backer rod as a packing material

Consult a 3M Authorized Fire Protection Products Distributor or Sales Representative

Equipment: 3M™ Smoke and Sound Tape may be applied by hand entirely or with the aid of a putty knife and roller.

Preparatory Work: Surfaces must be clean and frost free. For optimal adhesion, concrete surface should be a steel-floated smooth surface, or equivalent, that is free of chemical additives and/or compounds that could inhibit adhesion. For rougher surfaces (e.g. broom finished) tape, overlap onto substrate may need to be increased to achieve optimal adhesion. Check with your local 3M rep to determine acceptable finishes and required overlaps.

Installation Details: Installation details must be followed for each application. Install mineral fibre insulation in accordance with system details for density, depth and compressions requirements. Apply 3M™ Smoke and Sound Tape by

3M Fire Protection Products

3M™ Smoke and Sound Tape SST

hand. The tape should be applied over the insulation, adjacent substrates and penetrant (if applicable), maintaining all required overlaps in accordance with installation details.

Limitations: It is recommended that 3M™ Smoke and Sound Tape is applied at a temperature between -18°C (0°F) and 49°C (120°F). 3M™ Smoke and Sound Tape can be applied and expected to adhere to surfaces that are -18°C (0°F) or higher, providing that the surfaces are frost free, clean, and dust free.

NOTICE: This product is not for use as a commercial firestop.

Maintenance

No maintenance is expected to be required when installed in accordance with the 3M™ Smoke and Sound Tape Installation Guide. Once installed, if any section of the 3M™ Smoke and Sound Tape is damaged, the following procedure will apply: The insulation material must be inspected to ensure no moisture is evident. The open or damaged area must then be completely covered with new product, installed as detailed in the original installation instructions. The new product must overlap a minimum 25.4 mm (1 in.) onto the previously installed product.

Storage and Shelf Life

3M™ Smoke and Sound Tape should be stored indoors in dry conditions in the original packaging. To obtain best performance, use this product within 24 months from date of manufacture, which can be determined from the lot number (found on the label inside of the cardboard core). The label format is as follows: Name of tape – Work order number – Lot number (e.g. SST – 123456 – 634501).

Lot numbering (e.g. 634501): First digit = Last digit of year manufactured, second to fourth digits = Julian Date, Last two digits = Random to distinguish between lot numbers. 634501 = December 10, 2016

Availability

Available from 3M Authorized Fire Protection Products Distributors. For additional technical and purchasing information, call 1-800-328-1687 or visit 3M.ca/fire.

Safe Handling

Consult Article Information Sheet prior to handling and disposing of 3M™ Smoke and Sound Tape.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

3M Fire Protection Products

3M™ Smoke and Sound Tape SST

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Industrial Adhesives and Tapes Division
3M Canada
300 Tartan Drive
London, ON N5V 4M9

Phone 1-800-364-3577
Web 3M.ca/fire

3M is a trademark of 3M. Used under license in Canada.
© 2017, 3M. All rights reserved.
BA-17-24184 1706-09117 E